



## As flexible as your work.

With the VT860MKII headworn (with a cardioid capsule) Voice Technologies presents an excellent solution for TV, 2-way radio applications, public speaking and broadcast studio operations. It has been developed for outstanding clarity in noisy environments.

Much consideration has been put into the physical design of the VT860MKII. The flexible gooseneck enables the user to position the microphone for optimum sound and gain before feedback.

A one size fits all soft earpiece is connected to the integrated VT600 earphone. The headband is highly resistant to corrosion and is easy to clean.

Colors: beige or black

Application area: Broadcast - Video - Presentations

The VT860MKII comes in an elegant black case with the following accessories:

	EAR BEIGE	
	STRAP	Colors: beige or black
• )	WS800	Windscreen Colors: beige or black
	Case4	Size: 190x210x100mm

Audio Bauer Pro AG, Bernerstrasse-Nord 182, CH-8064 Zürich, Switzerland Phone: +41 44 432 32 30, Email: info@vt-switzerland.com

Specifications			
Generating Element:	Electret Condenser		
Polar pattern:	Cardioid		
Frequency Range:	100Hz- 10kHz		
Sensitivity (@1kHz):	-53dB ±3dB 1V/microbar (2.2mV/Pa)		
Noise Level	32dB "A" weighted		
Max. Input SPL:	120dB based on 9V supply		
Impedance:	2.8 to 6.8 kOhms, nominal 4.4 kOhms		
Bias/+VDC:	1.5V to 9.0V (max.)		
Dynamic Range:	88dB		
Signal Noise Ratio:	62dB @94dB SPL		
Color:	beige or black		
Cable:	Length 1,5m Ø 2mm		
Weight;	49 g		
Earphone:			
Element:	Subminiature Magnetic Receiver		
Frequency Range:	200Hz-8kHz		
Impedance:	500 kOhm		
Sensitivity:	104+/-3dB		
Distortion:	5% max.		
Colors:	beige or black		

Wiring Configuration (3-wire):	
Red	+VDC
Shield	Ground
Copper	NF
15 10 5 -10 -15 100 200 500 1000 2000 Frequency Response (	5000 10000 20000 Hz)